

**5-STAGE
REVERSE OSMOSIS SYSTEM**



**KINETICO A200
REVERSE OSMOSIS SYSTEM**



**KINETICO K5
REVERSE OSMOSIS SYSTEM**



MAINTENANCE	ANNUALLY	ANNUALLY	ANNUALLY OR EVERY 500 GALLONS, WHICHEVER HAPPENS FIRST
MANUFACTURER'S WARRANTY	1 YEAR PARTS AND LABOR	4 YEARS PARTS AND LABOR	10 YEARS PARTS AND LABOR
LIFE EXPECTANCY	UP TO 5 YEARS	UP TO 10 YEARS	UP TO 20 YEARS
NUMBER OF STAGES	UP TO 6	UP TO 6	UP TO 9
REDUCTION CAPABILITY	UP TO 96% FOR 5 YEARS	UP TO 96% FOR 10 YEARS	UP TO 99% FOR 20 YEARS
OPERATION	NON-ELECTRIC	NON-ELECTRIC	NON-ELECTRIC
NUMBER OF EXTERNAL CONNECTIONS	28-30	6-8	6-8
STORAGE TANK CAPACITY	1.75 GALLONS AIR-CHARGED TANK	1.75 GALLONS AIR-CHARGED TANK	3 GALLONS WITH QUICK FLOW™ TANK
FLOW RATE	AVERAGE 0.5 GALLONS PER MINUTE	AVERAGE 0.5 GALLONS PER MINUTE	HIGH WITH QUICK FLOW™ TANK 1.5 GALLONS PER MINUTE
STORAGE TANK REFILL TIME	60 MIN	60 MIN	30 MIN WITH QUICK FLOW™ TANK

**5-STAGE
REVERSE OSMOSIS SYSTEM**



**KINETICO A200
REVERSE OSMOSIS SYSTEM**



**KINETICO K5
REVERSE OSMOSIS SYSTEM**



NFS AND WQA CERTIFIED	✓	✓	✓
OPTIONAL MINERAL PLUS™ MODULE	✓	✓	✓
OPTIONAL ALKALINE WATER	✓	✓	✓
COMPATIBLE WITH INSTANT-HOT WATER DISPENSERS AND CHILLERS	✓	✓	✓
COMPATIBLE WITH REFRIGERATORS AND ICE-MAKERS	✓	✓	✓
OPTIONAL LEAK DETECTOR WITH AUTOMATIC SHUT-OFF	✓	✓	✓
AUTOMATIC RINSE OF THE RO MEMBRANE (MAIN FILTER) to prevent contaminant build-up, bacteria build-up, and premature membrane failure	✗	✗	✓
REMOVES TRACES OF RADIOACTIVE PARTICLES	✗	✗	✓
REMOVES TRACES OF PERCHLORATE	✗	✗	✓
REMOVES TRACES OF VOLATILE ORGANIC COMPOUNDS (VOC)	✗	✗	✓
REMOVES TRACES OF PHARMACEUTICALS	✗	✗	✓
FILTER-LIFE INDICATOR	✗	✗	✓
OPTIONAL QUICK FLOW™ TANK	✗	✗	✓
COMPATIBLE WITH ELECTRIC WATER IONIZERS SUCH AS KANGEN	✗	✗	✓